

ENTHERMO® III




The ENTHERMO® III can be used for caloric testing and ear syringing. It has three temperature settings (30°C - 37°C - 44°C) and a flow rate of 300 ml per minute. The set temperature is displayed on the device's display. The water pressure can be controlled from the button on the devices's handpiece. The set includes a bayonet and straight cannula and water inlet and outlet hoses for connection to a water supply with a minimum water pressure of 2 bar and a drain outlet.

Continuous flow system to prevent bacteria growth in water



Benefits at a glance

- Accurate electronic temperature control
- Three temperature settings
- Continuous water flow to prevent bacteria growth
- Pressure regulation from button on handpiece
- Overheating control
- Supplied with straight and bayonet cannulas
- Suitable for ear syringing and caloric testing
- Ready for use within 60 seconds after switching on
- LED indicator displays device status
- Safe and reliable
- Compact design



XX



Bayonet cannula and straight cannula

Technical specifications

Type (according IEC 60601-1) B

Classification (according IEC 60601-1)

Classification (according 93/42/EEG) IIa

Class IP22

Voltage 230 Volt A/C - 50 Hz

Maximum power consumption 1100 Watt

Temperature settings 30°C, 37°C, 44°C

Maximum supply water pressure6.0 barMinimum water pressure2.0 barWater pressure setting1.8 bar

Weight 3 kg

Product code: 844080 / III

ENTHERMO® III

Electronic warm water irrigator